



PRODUCT SELECTOR | THE BEST PRODUCT FOR YOUR FINAL FLOOR REQUIREMENTS

PRODUCT	DESCRIPTION	THICKNESS	FUNCTION						INSTALL GUIDE & SUBSTRATE					FLOORING MATERIAL (A = ADHERED F = FLOATED N = NAILED)												
			SOUND CONTROL UNDERLAYMENT	CRACK SUPPRESSION	COMFORT UNDERLAYMENT	ANTI-MICROBIAL PROTECTION	INTEGRATED MOISTURE BARRIER	THERMAL BENEFITS	ADHERED TO SUBSTRATE (A)	FLOAT OVER SUBSTRATE (F)	CONCRETE	GYPSUM / LIGHTWEIGHT CONCRETE	PLYWOOD / OSB	CERAMIC / NATURAL STONE	ENGINEERED WOOD	SOLID HARDWOOD	LAMINATE	CORK	BAMBOO	LVT / LVP	SHEET LINOLEUM	SHEET VINYL; FIBERGLASS - BACKED				
R12 STRESSCORK	CORK RUBBER CRACK SUPPRESSION UNDERLAYMENT	1.2 MM		●					A		●	●		A												
ECO2	AGGLOMERATED CORK & RECYCLED PUR & EVA FOAM GRANULE COMPOSITION	1.9 MM	●	●	●			●	A	F	●	●	●	A										A, F*		
T51	CORK RUBBER RESILIENT FLOORING UNDERLAYMENT	2.0 MM	●	●	●	●	●	●	A		●	●	●										A*,F	A	A*,F	
EZ-FLOOR LVT	AGGLOMERATED RECYCLED PUR FOAM GRANULE COMPOSITION	2.0 MM	●	●	●			●		F	●	●	●											A, F*		
PURC 200	AGGLOMERATED CORK & RECYCLED PUR FOAM GRANULE COMPOSITION	2.0 MM	●		●			●		F	●	●	●											A*,F	F	
CORKPLUS 250	AGGLOMERATED CORK & RECYCLED EVA FOAM GRANULE COMPOSITION	2.5 MM	●	●	●		●	●	A	F	●	●	●	A										A, F*	A, F*	A, F*
LVT TOTAL COMFORT	FLOATING LVT & MULTI-PURPOSE FLOATING FLOOR UNDERLAYMENT	1.8 MM	●		●	●	●	●		F	●	●	●		F	F	F	F	F	F	F					
QUIET COMFORTPLUS	WAVE TEXTURED PREMIUM UNDERLAYMENT W/ INTEGRATED VAPOR BARRIER	2.5 MM	●		●			●		F	●	●	●		F	F	F	F	F							
RR300	HIGH PERFORMANCE RECYCLED RUBBER	3.0 MM	●		●	●		●		F	●	●	●		A, F*	F, N*	F	F	F							
RC500	HIGH PERFORMANCE RECYCLED RUBBER & CORK UNDERLAYMENT	5.0 MM	●	●	●	●		●	A	F	●	●	●	A	A, F*	F, N*	F	F	F							
PR60	HIGH PERFORMANCE PROFILE WAVE TEXTURED UNDERLAYMENT	6.0 MM	●		●			●	A	F	●	●	●		A, F*	F, N*	F	F	F							
R60	PREMIUM CORK UNDERLAYMENT	6.0 MM	●	●	●			●	A	F	●	●	●	A	A, F*	F, N*	F	F	A, F*							
CRC950	HIGH PERFORMANCE COMPOSITE SHEET UNDERLAYMENT	9.5 MM	●	●	●			●	A		●	●	●	A	A		F									
RC1000	HIGH PERFORMANCE RECYCLED RUBBER & CORK COMPOSITION	10 MM	●	●	●	●		●	A	F	●	●	●	A	A	F, N*	F		A							
S130	PREMIUM CORK UNDERLAYMENT	12.7 MM	●	●	●			●	A		●	●		A	A	F, N*			A							

* Refer to installation recommendations per underlayment, finished flooring product and application.

